

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

12 **EUROPEAN PATENT APPLICATION**

21 Application number: 89108435.2

51 Int. Cl. 4: **B65D 55/06 , G09F 3/02 ,
B65D 33/34 , B65D 27/30**

22 Date of filing: 10.05.89

30 Priority: 13.05.88 US 193799
31.03.89 US 334084

43 Date of publication of application:
15.11.89 Bulletin 89/46

54 Designated Contracting States:
AT BE CH DE ES FR GB GR IT LI LU NL SE

71 Applicant: **SEALCRAFT CORPORATION**
5029 Industrial Road
Farmingdale New Jersey 07727(US)


72 Inventor: **Ewan, Frederick R.**
145 Spinnaker Way
Neptune New Jersey 07753(US)

74 Representative: **Minoja, Fabrizio**
Studio Consulenza Brevettuale Via Rossini,
8
I-20122 Milano(IT)

54 **Tamper indicating containers and seals.**

57 A seal comprising a substrate (124) which is at least translucent to light having a transparent masking material (132) disposed in an indicia-defining pattern on the inner surface (130) of the substrate. A colorant layer (134) is disposed over the masking material and extends beyond the pattern. There is an adhesive (138) disposed at least over the area of the colorant. The present invention also includes a tamper indicating opaque container (10) such as an envelope or carton has a window (20) defined within the closure flap (14). A translucent or transparent panel (24) overlaying the window has a transparent masking material (32) of low adhesion properties disposed in an indicia-defining pattern. A colorant layer (34) is disposed over the transparent masking material and an adhesive (38) in turn is disposed over the colorant layer and transparent masking material. Upon unsealing of the closure flap, the adhesive dislodges the colorant from the panel within the area of the indicia-defining pattern defined by said masking material with the dislodged material remaining on the container, forming two tamper indicating indicia.

FIG-13



TAMPER INDICATING CONTAINERS AND SEALS

This is a continuation-in-part of Serial No. 07 193,799, filed May 13, 1988.

BACKGROUND OF THE INVENTION

A variety of devices designed to reflect unauthorized tampering have been described previously. A number of proposals for tamper-proof labels, for example, which are designed for attachment to other objects, have been described.

U.S. Patent No. 1,003,443 to Erickson discloses a stamp or label having complementing films, one of which adheres to a receiving surface to discourage second use of the stamp or label.

U.S. Patent No. 3,487,567 to Waybright discloses an emblem or label for a vehicular window having an adhesive on one side of a transparent sheet and an indicia on the other, with an opaque layer carrying special indicia affixed to the transparent sheet.

U.S. Patent No. 3,631,617 to Pekko discloses a tamperproof label having a transparent self-supporting film which is imprinted with a first visual indicia. There is a masking surface which is in contact with at least part of the surface of the transparent substrate. The masking surface is imprinted with a visual indicia. An adhesive layer is applied having a first surface in contact with the substrate and the masking surface, the second surface of the adhesive layer contacting a substrate. It is a goal of the label of this patent to provide a visual imprinting when the label is sealed in place. When the label is applied to a substrate and thereafter removed, a portion of the indicia remains on the substrate and a portion is removed with the film.

U.S. Patent No. 4,082,873 to Williams discloses switchproof laminated labels having a transparent plastic film on which an indicia is imprinted in reverse and which is coated with an adhesive. The printing has a greater affinity for the adhesive than the film so that when mounted on an object and then removed, a tamper indicating amount of the printing remains on the object.

U.S. Patent No. 4,180,929 to Schultz discloses tamper indicating multilaminate labels having two sets of indicia, one of which is rendered visible upon tampering and a second which is visible regardless of tampering.

U.S. Patent No. 4,608,288 to Spindler discloses tamper proof labels having an irreversibly stretchable cover foil adhesively joined to a base foil with varying degrees of adhesion.

A number of references also describe tamper indicating tapes which are applied to containers and provide means indicating when the seal has been broken.

U.S. Patent No. 3,923,198 to Brochman discloses a tape which opacifies when stressed.

U.S. Patent No. 3,935,960 to Cornell discloses a tamper indicating tape having encapsulated dye in a binder material.

U.S. Patent No. 4,557,505 to Schafer discloses a tape which opacifies when stressed and which carries contrasting colored indicia.

U.S. Patent No. 4,652,473 to Han discloses a tape of two different materials which is heat shrunk onto a container.

Such tapes and labels must be applied to the outside of containers in a separate step. Moreover, these devices can be removed in the course of intentional tampering and the tampering indicia then covered, as with opaque tape, so to conceal the evidence of tampering. Various attempts have been made to incorporate tamper indicating means into the actual product so as to eliminate the need for affixing a label or tape.

U.S. Patent No. 2,181,252 to Vogel discloses a safety envelope having two flaps, one of which carries a printing in ink which is soluble in the same solvents as is the envelope adhesive.

U.S. Patent No. 3,933,304 to Judd discloses bags for bank notes which are heat sealed at a position adjacent to an area of printing so that the bags cannot be opened without mutilating the printing.

U.S. Patent No. 4,505,399 to Weiner discloses a closure which includes a material sensitive to ambient conditions such as light or oxygen.

U.S. Patent No. 4,718,553 to Adamoti discloses tamper evident packaging for cartons in which a transparent film overwraps the carton and is secured to ink on the carton in selected different patterns.

U.S. Patent No. 4,721,217 to Phillips discloses a cap having a pair of layers providing a color shift which is destroyed or modified when the layers are separated.

U.S. Patent Nos. 4,709,396 and 4,709,397 to Voshall disclose a tamper evident envelope in which a pressure sensitive seal along one edge contains a hidden message. Two cohesive layers, one continuous and the other non-continuous, are employed with the latter creating voids appearing as reverse drop-out patterns when the two cohesive layers are separated.

These devices generally involve either complicated manufacturing steps or utilize relatively

expensive materials. This is particularly true for devices in which the tamper-indicating means are incorporated into the actual product. Devices such as those disclosed by Voshall in U.S. Patent Nos. 4,709,396 and 4,709,397, for example, require two cohesive layers which must be separated prior to use, as well as inner paper liners to conceal the contents of the package since the outer sheet must be transparent to reveal the tampering indicia. In addition, many tamper indicating devices, particularly tapes, so complicate the overall packaging that the intended user may encounter difficulty simply trying to open the package, often a serious problem with the elderly.

SUMMARY OF THE INVENTION

The present invention is a seal comprising a substrate preferably being translucent or transparent to light, having an outer surface and an inner surface. A transparent masking material is disposed in an indicia-defining pattern on the inner surface of the substrate. The masking material possesses low adhesion properties to the material of said substrate. A colorant layer is disposed on the inner surface of the substrate over the transparent masking material and can extend beyond the indicia-defining pattern of the masking material. An adhesive is disposed over at least the area in which the colorant layer and transparent masking material are disposed.

The present invention also includes an opaque container comprising a body portion and at least one integrated sealable closure flap. The closure flap has an exposed outer surface and a sealable inner surface. A window portion is defined within an area of at least one outer closure flap. The window portion registering with a surface of the container upon closure of said flap.

There is a translucent or transparent panel overlaying the window portion and being affixed across at least a portion of its perimeter to a surface of the closure flap. The panel has an outer surface and an inner surface and possesses surface dimensions greater than those of the window portion such as to define a perimeter portion extending beyond the edges of the window portion.

A transparent masking material is disposed (i) in an indicia-defining pattern (ii) on the inner surface of the translucent or transparent panel opposite the exposed outer surface of said closure flap and (iii) within an area registering with said window portion. The masking material possesses low adhesion properties to the material of said translucent or transparent panel.

A colorant layer is disposed on the inner sur-

face of the translucent or transparent panel over the transparent masking material and extending beyond the indicia-defining pattern of the masking material.

An adhesive is disposed over at least the area in which said colorant layer and transparent masking material are disposed. The adhesive is registered with a surface of the container upon closure of said flap and operable upon unsealing of said flap to dislodge said colorant from said panel within the area of the indicia-defining pattern defined by said masking material.

The present invention results in a sealed article whether in the embodiment of a seal or a tamper proof container. The substrate layer has relatively greater adhesion to colorant layer than the masking layer.

When the substrate layer is lifted, the unmasked colorant layer is removed with the substrate leaving the masking material and colorant layer beneath the masking material on the article sealed. The translucent or transparent substrate, prevents the seal from substrate from being replaced in its original condition. The seal irreversibly indicates when it is opened. The seal is not apparently tamper proof to the observer.

BRIEF DESCRIPTION OF THE DRAWINGS

FIGURE 1 is a partial plan view of a container of the envelope type prior to sealing.

FIGURE 2 is a partial plan view of the envelope shown in FIGURE 1 in its sealed configuration.

FIGURE 3 is a partial plan view of the envelope shown in FIGURE 2 which, however, has been opened after being sealed.

FIGURE 4 is a partial plan view of the envelope shown in FIGURE 3 which has been resealed after being opened.

FIGURE 5 is a vertical section view taken along line V-V of FIGURE 1.

FIGURE 6 is a vertical section view taken along line VI-VI of FIGURE 2.

FIGURE 7 is a vertical section view taken along line VII-VII of FIGURE 3.

FIGURE 8 is a vertical section view taken along line VIII-VIII of FIGURE 4.

FIGURE 9 is a perspective view of a further embodiment in which the container is a packaging box.

FIGURE 10 is a perspective view of a further embodiment in which the container is a corrugated carton.

FIGURE 11 is an alternate embodiment of the present invention.

FIGURE 12 is a further embodiment of the present invention.

FIGURE 13 is a sectional view of the seal of the present invention.

FIGURE 14 is a plan view of an embodiment of the seal of the present invention, where the seal is non-continuous and is on a continuous carrier strip.

FIGURE 15 illustrates a seal partially removed from an envelope.

FIGURE 16 is a side view, schematically illustrating a continuous seal strip in a roll.

FIGURE 17 is an alternate embodiment of the seal of the present invention.

FIGURE 18 is a sectional view of a further embodiment of the invention.

FIGURE 19 is a plan view of a container utilizing the seal of FIGURE 18.

FIGURE 20 is a sectional view of another embodiment of the present invention.

DETAILED DESCRIPTION

The present invention pertains to tamper-indicating containers and seals of simplified design and reduced cost. The tamper-indicating device is incorporated into the container itself and requires no additional packaging, thereby rendering the package easily opened by the intended user while irreversibly displaying the tampering indicia, should such tampering have occurred, whether the container is opened or closed. Moreover, the device permits the use of opaque materials. The nature of the invention will become more apparent from the following description and the accompanying drawings.

Referring now to FIGURES 1-8, opaque container 10 has a body portion 12 and at least one integrated sealable closure flap 14. While the invention is illustrated here with respect to an envelope, it is equally useful in other container types, such as folding cartons, corrugated boxes having integrated sealable closure flaps, conventional box packaging, and the like, as shown for example in FIGURES 9 and 10. The container can be constructed of conventional materials such as paper, paperboard, corrugated paper, flexible plastic, as for example spun-bonded polyethylene such as is sold by Dupont under the trademark Tyvek, and the like.

Closure flap 14, which ideally is opaque, has an exposed outer surface 16 and a sealable inner surface 18. Defined within an area of closure flap 14 is a window portion 20, here an aperture. Window 20 is positioned within closure flap 14 so as to register with a sealable surface 22 of container 10

upon closure of flap 14. Its dimensions are largely a matter of choice although it should not be so large as to distort or substantially weaken flap 14 nor so small as to permit entry into the container without involvement of the area occupied by the window.

Extending beyond the edges of window 20 is panel 24. Panel 24 can be fabricated from conventional materials such as films of polyester, polyethylene, polypropylene, copolymers thereof, and the like. For reasons discussed below, it can be fully transparent but is preferably translucent. It can be provided with a matte or similar dull finish to be translucent, particularly if the material used is normally transparent.

Panel 24 is cut in surface dimensions greater than those of window 20 so that it can overlay window 20 and thereby define a perimeter portion 26 extending beyond the edges of window 20. Panel 24 has an outer surface 28 and an inner surface 30 and is affixed, as with an adhesive (not shown) having a strong affinity for both the panel and the material of the flap, across at least a portion of its outer surface 28 in perimeter portion 26 to inner surface 18 of closure flap 14. Alternatively, the panel can be affixed to the window by welding, stitching, or equivalent means.

Disposed in an indicia-defining pattern on inner surface 30 of panel 24 and within an area registering with window 20 is transparent masking material 32. Masking material 32 possesses low adhesion properties to the material of translucent panel 24, as for example a silicon oil. It can be applied flexographically or printed by offset or letterpress techniques in an indicia-defining pattern corresponding to appropriate symbols or words such as "VOID" or "OPENED" in mirror image.

A colorant layer 34 is disposed on inner surface 30 of panel 24 over and extending beyond the indicia-defining pattern defined by masking material 32. The colorant layer can be an ink formulation, the composition of which will depend upon the composition of panel 24. Thus if panel 24 is fabricated from polyester, the colorant can be a nitrocellulose or acrylic ink.

In the embodiment shown in FIGURES 5, 6, 7, and 8, a primer layer 36 is disposed between masking material 32 and colorant layer 34 in an area at least coextensive with the area in which colorant layer 34 is disposed. Primer layer 36 facilitates adhesion of colorant layer 34 to panel 24 in those areas in which masking material 32 is not present. When the colorant material has a high affinity for the material of panel 24, primer layer 36 is not always needed and can be eliminated.

Adhesive 38 is disposed over at least a portion of inner surface 18 of closure flap 14. The portion over which adhesive 38 is disposed will include at

least the area in which colorant layer 34 and transparent masking material 32 are disposed. Adhesive 38 is operable first to seal closure flap 14 to a sealable surface 22 of container 10 upon closure of flap 14 as shown in FIGURE 6. In addition, upon subsequent unsealing of flap 14 as shown in FIGURE 7, adhesive 38 dislodges portions 40 of the composite including colorant layer 34 (and material from primer layer 36 if present) from panel 24 and retain these dislodged portions on sealable surface 22 of container 10. Since masking material 32 possesses low adhesion properties to the material of translucent or transparent panel 24, differential adhesion will occur, with portions of colorant layer 34 being dislodged, as determined by the indicia-defining pattern defined by masking material 32.

The masking material, colorant, and any primer are applied wet to panel 24 so as to develop an interface more intimate than that which would result from dry application of the same components to panel 24. Consequently, attempted resealing after opening as shown in FIGURES 7 and 8, will not achieve the same interface and air spaces, shown generally as 44 in FIGURE 8, will remain between colorant layer 34 and panel 24 in the indicia-defining pattern previously defined by masking material 32, thereby creating a color differential. The generation of these air spaces is also facilitated by the fact that dislodgement of the composite in the areas of the masking material does not produce a completely even boundary so that upon attempted resealing, the dislodged composite portions 40 will not fully complement voids 42 in the composite remaining on panel 24. The colorant layer 34 can comprise multiple layers, preferably laminated together, of more than one contrasting color to emphasize the voids. Thus the indicia will be irreversibly displayed through window 24, as shown in FIGURE 4.

In the embodiment shown in FIGURES 5-8, adhesive 38 can be of the pressure sensitive type. A release strip 48 (shown in Figure 5) of a material having a low affinity for the adhesive can be affixed to the adhesive to protect the same prior to sealing, the release strip being removed without disturbing the underlying composite and discarded when the envelope or container is to be sealed.

The adhesive layer 38 can be made of an adhesive composition such as acrylic-based adhesives which optionally contain microencapsulated dye. The dislodged portion 40 adheres to the sealable surface 22 at adhesive layer 38. Any attempt to rub off, or erase the dislodged portion will cause the capsules containing the dye to rupture and release the dye. The dye will discolor the sealable surface 22 evidencing tampering. Preferably the dye in the encapsulated dye is a matching color to colorant layer 34.

FIGURE 9 depicts a further embodiment in which the tamper indicating composite is incorporated in a packaging box. In such an embodiment, which is shown as having been opened after having been sealed (analogous to FIGURE 7), the container is sealed by the manufacturer or distributor prior to sale and adhesives other than those of the pressure sensitive type can be used, as for example acrylics, water base glues, two-part latex, etc., with appropriate selection of the colorant, masking material, and primer, if any. Since there may be several closure flaps 50, 52 and 54, the window is placed on that flap 54 having an exposed outer surface relative to the container. The contiguous flap 52 then becomes the sealable inner surface.

A totally analogous structure can be used for corrugated cartons. Where, however, it is desired to provide additional rigidity to the closure flap prior to sealing, the embodiment of FIGURE 10 can be employed. Thus translucent or transparent panel 64 is affixed to the outside of the closure flap 67 in which die-cut slug 66 has been defined as by a knife-cut. In addition to the adhesive between the panel and the outside surface of the flap, a second layer of adhesive (not shown) will be applied between the inner surface of the flap and the sealing surface of the container, such as inner panel 68. Prior to sealing, slug 66 provides additional strength to panel 64. Upon sealing panel 64, including slug 66, to inner panel 68 through the second adhesive and thereafter opening the container, slug 66 will remain on panel 68 with the tamper indicating indicia being displayed thereon.

Additional embodiments of the invention are illustrated in FIGURES 11-12. These figures correspond to FIGURE 5. Elements which are the same have the same reference characters and reference is made to the corresponding description.

FIGURE 11 is directed to a generally transparent or translucent container 110. The container is preferably made of a polymeric material, preferably a thermoplastic polymeric material. Preferred materials are polymer film or sheet made of: polyolefins such as polyethylene, ethylene vinyl acetate copolymers, ethylene acrylic acid copolymers; polypropylene; acrylic polymers; vinyl polymers such as polyvinyl fluoride, polyvinyl chloride, and the like; cellulose acetate; polycarbonates; polyesters; polyethanes; polysulfones; styrene polymers, and the like. Useful films and sheets are from 0.0015 to 0.5 inches and preferably from 0.001 to 0.05 inches thick. Preferred film is from 0.001 to 0.01 inches thick and preferred sheet is from 0.01 to 0.25 inches thick.

The body portion 112 and closure 114 are both transparent or translucent and preferably integrally connected as one unit. There is an indicia defining

pattern disposed on the inner surface 130 of closure 114. Preferably, the indicia defining pattern extends across the full width of closure 114 parallel to opening between sealable surface 122 and sealable inner surface 118.

In this embodiment, the whole closure 114 seals the container 110. The indicia forming defining pattern directly adheres to closure 114. Since the closure 114 itself is translucent or transparent, there is no need for a separate panel 24, as in the embodiment of FIGURES 5 and 6.

FIGURE 12 is a further embodiment in which container 210 has a separate opaque body portion 212 with a separate transparent or translucent closure 214. The closure is attached to the body. In the embodiment illustrated, the closure 214 is attached to the body 212 along a closure side 217 of the container. The closure can be attached by a suitable means, such as adhesive at the interface 217 between the closure side 217 and closure 214. Preferably the closure can be laminated as an additional layer onto the closure side 217. It can be located inside or outside of the container 210. The closure 214 can be made of materials and thicknesses of the type used in the embodiment shown in FIGURE 11.

Reference is made to FIGURES 13-16 which illustrate a further embodiment of the present invention in the form of a seal which is generally shown as reference character 100. Although embodiments incorporating tamper indicating means have the advantage of eliminating the need for separate labels or tape, the present invention has resulted in an improved seal. The seal 100 contains corresponding elements to the embodiment illustrated in FIGURES 5-8 and operates in a corresponding way. Upon being used, there is no indication that the seal will permanently indicate when it has been lifted from the article to be sealed. When the seal is opened, there is a permanent indication that it has been opened.

The seal comprises a substrate 124 which has an outer surface 128 and an inner surface 130. Substrate 124 can utilize materials similar to those employed for panel 24. Preferably, substrate 124 is made of a flexible, translucent polymeric film or sheet. Useful polymers for substrate 124, as well as panel 24, include but are not limited to self-supporting films made of polyethylene; ethylene vinyl acetate copolymers; ethylene acrylic acid copolymers, and the like; propylene based polymers; acrylic polymers; vinyl polymers such as polyvinyl fluoride, polyvinyl chloride, and the like; cellulose acetate; polycarbonates; polyesters; polyethers; polysulfones; styrene polymers. Substrate 124 is typically from 0.0005 to 0.5 in., preferably from 0.001 to 0.05 inches thick. Depending on the article to be sealed, substrate 124 can be made

of flexible polymer film preferably from 0.001 to 0.01 in. Polymer sheet is preferably 0.01 to 0.25 inches thick. The thickness and material of the substrate can be varied depending upon the article to be sealed.

Disposed in an indicia-defining pattern on inner surface 130 of panel 124 and is substantially transparent masking material 132. Masking material 132 possesses low adhesion properties to the material of substrate 124. It can be made of the same type of material used to make masking material 32, and can be applied by the same process.

A colorant layer 134 is disposed on inner surface 130 of substrate 124 over and extending beyond the indicia-defining pattern defined by masking material 132. The colorant layer can be the same type of material as colorant layer 34. The colorant layer 134 preferably extends over substantially all, and more preferably over the whole area of the substrate 124.

Optionally, a primer layer 136 is disposed between masking material 132 and colorant layer 134 in an area at least coextensive with the area in which colorant layer 134 is disposed. Primer layer 136 facilitates adhesion of colorant layer 134 to substrate 124 in those areas in which masking material 132 is not present. When the colorant material has a high affinity for the material of substrate 124, primer layer 136 is not needed and can be eliminated.

Adhesive 138 is disposed over at least a portion and preferably over the whole area in which colorant layer 134 and transparent masking material 132 are disposed.

The adhesive 138 is operable first to seal the article to be sealed. For example, FIGURE 15 illustrates a conventional envelope 160 having a closure flap 162. A closure edge 164 is defined where the flap 162 meets the body 166 of the envelope 160. The seal 100 can be used to seal the envelope at closure edge 164.

Upon subsequent unsealing of seal 100 as shown in FIGURE 15, the substrate 124 is lifted away from the article such as envelope 160. The colorant 134, and optionally primer layer 136, have relatively greater adhesion to substrate 124 than to adhesive layer 138 and the adhesive layer 138 to the article, such as envelope 160, which is being sealed. Therefore, upon lifting the substrate layer 124, unmasked colorant layer 134 adheres to and is removed with the substrate 124. Portions 140 of the composite including colorant layer 134 (and material from primer layer 136 if present) continue to adhere to the article such as envelope 160, which is sealed. Since masking material 132 possesses low adhesion properties to the material of translucent substrate 124, differential adhesion will occur, with portions of colorant layer 134 being

dislodged, as determined by the indicia-defining pattern defined by masking material 132. This residual portion 140 can be adhered to the article to be sealed indicating the article was tampered with.

As in the embodiment shown in FIGURES 5-8, adhesive 138 can be any suitable adhesive. It can be a water initiating adhesive. Preferably the adhesive is a pressure sensitive type. When a pressure sensitive type of adhesive is used, a release type carrier web is useful to support the seal. The release carrier web supports the seal in contact with the adhesive layer 138. Release web 150 of a material has a low affinity for the adhesive and can be affixed to the adhesive to protect the same prior to sealing, the release strip being removed with substantially no disturbance of the adhesive layer and the underlying composite.

The adhesive layer 138 is made of adhesive composition which optionally contains encapsulated dye. The dislodged portion 140 adheres to a sealable surface such as an envelope 160 at adhesive layer 138. Any attempt to rub off, or erase the dislodged portion will cause the capsules containing the dye to rupture and release the dye. The dye will discolor the sealable surface evidencing tampering. Preferably the dye in the encapsulated dye is a matching color to colorant layer 34.

The seal 100 has a colorant 134 applied so that the transparent masking material is not apparent when the seal is applied to an article such as envelope 160 shown in FIGURE 12. It is only when the seal is separated from the article that the indicia formed by the masking material 132 become irreversibly apparent. The colorant in the colorant layer between the substrate 124 and the adhesive layer 138 preferentially adheres to the substrate layer 124 rather than the article, except where there is transparent masking material 132. The colorant adheres to the article such as envelope 160 rather than the substrate layer 124 because of the relatively low adhesion level between the colorant layer 134 and the masking layer 132 compared to the colorant and the adhesive layer 138 which itself adheres to the article, i.e. envelope 160.

The seal itself can be in any suitable form depending upon the article to be sealed. The seal can be in noncontinuous shapes useful for specific articles to be sealed. Useful shapes are squares or rectangles such as shown as seals 100 in FIGURE 12. Here the seal 100 is on a carrier web or strip such as carrier strip 150. Carrier strip 150 is adjacent to and releasably adheres to adhesive layer 138. The seal 100 is easily removed from carrier strip 150 with substantially no disturbance to adhesive layer 138 or to the seal 100. Preferably, there is no disturbance to the adhesive layer or the seal by removal from the carrier strip.

FIGURE 15 illustrates rectangular shaped seal 100 being used to seal envelope 160. The flap 162 is folded to close envelope 160. The flap can adhere to the body 166 of the envelope such as shown in FIGURES 1 AND 2. A seal 100 is placed over closure sealing edge 164 where the edge of the flap 162 meets the body of the envelope. The tamper evidencing indicia 140 resulting from the masking material 132 is not apparent. Upon separating of the seal 100 from the envelope, the adhesive 138 adheres to the envelope where it was not lifted from the envelope by preferentially adhering to substrate 124. The colorant 134 remains adhered to the envelope as evidence that the seal was removed.

The noncontinuous seal embodiment illustrated in FIGURES 14 and 15 is shown in a preferable and useful rectangular shape. It is recognized that other shapes can be used depending upon the article and for ornamental design. Useful shapes include squares, rectangles, circles and ornamental shapes such as letters, numbers, trademarks, and the like.

In an alternate embodiment, the seal 100 can be continuous such as a continuous strip or tape as illustrated in FIGURE 16. The tape can have a carrier web such as carrier strip 150 in FIGURE 14 except that seal 100 is a continuous strip. The substrate 124 can be made of a material which has an outer surface 128 which has sufficiently low adhesion to the adhesive layer 138 to enable the continuous seal to be rolled with the adhesive layer adjacent to the outer surface 128 so that the strip can be unrolled with substantially no disturbance to the adhesive layer and the seal.

FIGURE 17 is an alternate embodiment of the seal of the present invention. The seal 175 is useful to seal containers having rough surface including fibrous and corrugated surfaces.

The seal 175 in FIGURE 17 has common reference characters for common elements as the seal illustrated in FIGURE 13. There additionally is a barrier layer 177 adjacent to the adhesive layer 138 on the side of the adhesive layer 138 opposite the colorant layer 134.

There is a strong adhesive layer 179 adjacent to the barrier layer 177 on the side of the barrier layer opposite the adhesive layer 138.

The barrier layer 177 is thereby located between adhesive layer 138 and strong adhesive layer 179. The barrier layer 177 has relatively greater adhesion to the strong adhesive layer 179 than to the adhesive layer 138. The strong adhesive layer 179 can be supported on release web 150.

In operation, release web 150 is removed revealing strong adhesive layer 179. Strong adhesive layer 179 is placed on a surface to be sealed. If the seal is tampered with the substrate layer 124 is

lifted away from the surface of the sealed article. The composite of the colorant 134, optionally primer layer 136 and adhesive layer 138, have relatively greater adhesion to each other and to substrate 124 than to the barrier layer 177. Upon lifting substrate 124, unmasked colorant layer 134 adheres to and is removed with substrate 124. Portions of the composite which were masked including colorant layer 134 (a material from primer layer 136 if present) continue to adhere to the barrier layer 177.

The barrier layer 177 preferentially adheres to the strong adhesive layer 139 rather than being lifted with adhesive layer 138 when the substrate 134 is lifted. This leaves behind a desired indicia formed by the masking materials 132.

The strong adhesion can be a suitable adhesive such as acrylic based adhesives, so long as it sealingly adheres to the rough surface and has greater adhesion to the rough surface to be sealed and barrier layer 177 than adhesive layer 138 has to the barrier layer 177.

The barrier layer can be a polymer-based coating up to 0.1 inches thick, preferably up to 0.01 inches thick. Alternatively, it can be a layer of self-supporting polymer film, or multilayered laminate, foil, paper or the like. The requirement of the barrier layer is that it have greater adhesion to the strong adhesive layer 179 than to the adhesive layer 138. In effect, the combination of strong adhesive layer 179 and barrier layer 177 provides a base on rough surfaces for the seal of the present invention.

Preferably, barrier layer 177 is brittle, and more preferably, more brittle than adhesive layer 179. Any attempt to remove the seal 175 would result in the barrier layer breaking into small pieces. This construction enables the seal to be applied to rough surfaces.

In a further embodiment, the seal can be incorporated between opposing, sealingly connected walls of a sealed container. Typically, opposing walls can be connected by adhesives or heat. The tamper indicating seal is located in the sealingly connected area. Once the sealed area is separated dislodged portions of the seal will evidence opening.

Typical embodiments are illustrated in FIGURES 18 and 19. Seal 185 is located in the sealingly connected area of opposing connected walls of a film bag 187 such as used with snacks, potato chips, pretzels etc. Seal 185 contains elements corresponding to the embodiment illustrated in FIGURES 5-8 and operates in a corresponding way. Corresponding elements have the same reference characters.

Bag 187 typically is constructed from one or more layers of polymeric material, with opposing

walls 189 and 191 having inner surfaces 193 and 195, respectively. Such bags have at least one sealed end and typically opposite sealed ends 197. One such end 197 is shown in FIGURE 18. The bag can be a tubular extrusion or have a seam 194 extending longitudinally from end to end. The inner surfaces 193 and 195 are closed at or near the end 197. The inner surfaces 193 and 195 at the end 197 are connected by a suitable adhesive, or in the case of thermoplastic film, heat sealed to sealingly enclose an enclosed volume 201. The walls 189 and 191 are connected at end 197 along a common area 199 to define enclosed volume 201. The adhesive layer 38 can be the same adhesive as the adhesive used to seal the opposing connected walls.

The seal 185 of the present invention can be located between walls 189 and 191 in the common area 199. Preferably, the seal extends along the full length of the common area 199, parallel to sealed end 197. Separation of connected walls 189 and 191 at the seal 187 will cause the seal to be broken leaving indicia forming dislodged portions such as dislodged portions 40 shown in FIGURE 7.

The present invention includes a further embodiment illustrated in FIGURE 20 in which the seal can be located at the interface of a container and a closure for the container. Container 200 comprises a main receptacle 202 and a closure 203. In the embodiment shown in FIGURE 20, the closure is a liner layer which can be a thin film or film laminate layer 203. Receptacle 202 optionally can be additionally covered by lid 204. Receptacle 202 has a wall 205 and a lip area 206 at the edge of the wall 205. The closure 203 and lip area 206 of the receptacle have corresponding opposing surfaces, such as closure opposing surface 208 and lip opposing surface 210. Seal 212 of the present invention is located between opposing surfaces 208 and 210. Seal 212 contains elements corresponding to the embodiment illustrated in FIGURES 5-8 and operates in a corresponding way. Corresponding elements have the same reference characters. Closure 203 and receptacle 202 are sealingly connected at opposing surfaces 208 and 210. The seal 212 can be used to connect surfaces 208 and 210, and/or surfaces 208 and 210 can be connected by the use of an adhesive and/or by heat sealing the two surfaces in such a manner so as to perform the same function as adhesive element 38.

In an alternate embodiment, the container of FIGURE 20 has no liner and the seal 212 is located between, and in contact with, lip area 206 and lid 204. Preferably there are flat, opposing lip surface 210 and opposing lid surface 208. The lid 204 has a shape corresponding to the shape of receptacle 202. The lip 206 has a flat lip extension 214 extending radially from the wall 205 of receptacle

202. The lid 204 extends to the outer edge of lip extension 214 and has a lip interlock means such as extension 218 which extends generally axially from the lid 204 toward the receptacle 202. There can be a locking ridge 220 at the end of extension 218. The locking ridge generally extends radially toward the receptacle. The outer edge of lip extension 214 is interlocked between surface 208, extension 218 and ridge 220 when the receptacle 202 is closed with the lid 204.

The receptacle 202 is sealed with seal 212 being at between at least part of opposing surfaces 208 (or 208') and 210. When the lid is removed the seal will be broken leaving indicium formed by dislodged portion such as dislodged portion 40 drawn in FIGURE 7.

While exemplary embodiments of the invention have been described, the scope of the invention is to be determined from the following claims.

Claims

1. An article comprising:

(a) first and second surfaces capable of being connected to one another, said first and second surfaces being defined on separate areas of the same article or on separate articles;

(b) a transparent masking material disposed in an indicia-defining pattern on an area of the first surface, said masking material possessing low adhesion properties to the material of the second surface;

(c) a colorant layer disposed over the transparent masking material on said first surface and extending beyond the indicia-defining pattern of the masking material; and

(d) an adhesive disposed over at least the area in which the colorant layer and transparent masking material are disposed, said adhesive being operable to said first and second surface, and upon unsealing, to dislodge said colorant from said first surface within the area of the indicia-defining pattern defined by said masking material.

2. A container comprising:

(a) a first and a second opposing walls, each having an inner surface, and said container having at least one sealed end wherein the opposing walls are capable of being connected;

(b) a transparent masking material disposed (i) in an indicia-defining pattern (ii) on the inner surface of the first opposing wall and (iii) the masking material possessing low adhesion properties to the material of the opposing wall;

(c) a colorant layer disposed on the inner surface of the closure flap over the transparent masking material and extending beyond the indicia-

defining pattern of the masking material; and (d) an adhesive disposed over at least the area in which the colorant layer and transparent masking material are disposed, the adhesive being registered with the second opposing wall of the container upon the first and second opposing wall being connected at said sealed end and operable upon unsealing of said opposing walls to dislodge said colorant within the area of the indicia-defining pattern defined by said masking material.

3. A container comprising:

(a) a receptacle portion and at least one closure, the receptacle having a wall, and a lip area at the edge of the wall, the lip area having a lip surface, the closure has a closure opposing surface corresponding to and opposite the lip surface; the lip surface and the closure surface being opposing surfaces;

(b) a transparent masking material disposed (i) in an indicia-defining pattern (ii) on the at least one opposing surface and (iii) the masking material possessing low adhesion properties to the material of the at least one opposing surface;

(c) a colorant layer disposed on at least one opposing surface over the transparent masking material and extending beyond the indicia-defining pattern of the masking material; and

(d) an adhesive disposed over at least the area in which the colorant layer and transparent masking material are disposed, the adhesive being registered with at least one opposing surface of the container and operable upon unsealing of said closure to dislodge said colorant from said surface within the area of the indicia-defining pattern defined by said masking material.

4. A container comprising:

(a) a body portion and at least one integrated sealable closure flap, said closure flap having an exposed outer surface and a sealable inner surface;

(b) a transparent masking material disposed (i) in an indicia-defining pattern (ii) on the inner surface of the closure flap and (iii) the masking material possessing low adhesion properties to the material of the closure flap;

(c) a colorant layer disposed on the inner surface of the closure flap over the transparent masking material and extending beyond the indicia-defining pattern of the masking material; and

(d) an adhesive disposed over at least the area in which the colorant layer and transparent masking material are disposed, the adhesive being registered with a surface of the container upon closure of the flap and operable upon unsealing of said flap to dislodge said colorant from said flap

within the area of the indicia-defining pattern defined by said masking material.

5. The container of claim 4 wherein the body portion is transparent or opaque and the closure flap is transparent or translucent.

6. An opaque container comprising:

(a) a body portion and at least one integrated sealable closure flap, said closure flap having an exposed outer surface and a sealable inner surface;

(b) a window portion defined within an area of at least one outer closure flap, said window portion registering with a surface of the container upon closure of said flap;

(c) a translucent or transparent panel having an outer surface and an inner surface and possessing surface dimensions greater than those of said window portion such as to define a perimeter portion extending beyond the edges of the window portion, said panel overlaying said window portion and being affixed across at least a portion of its perimeter to a surface of the closure flap;

(d) a transparent masking material disposed (i) in an indicia-defining pattern (ii) on the inner surface of the translucent or transparent panel opposite the exposed outer surface of said closure flap and (iii) within an area registering with said window portion, said masking material possessing low adhesion properties to the material of said panel;

(e) a colorant layer disposed on the inner surface of the translucent or transparent panel over the transparent masking material and extending beyond the indicia-defining pattern of the masking material; and

(f) an adhesive disposed over at least the area in which said colorant layer and transparent masking material are disposed, said adhesive being registered with a surface of the container upon closure of said flap and operable upon unsealing of said flap to dislodge said colorant from said panel within the area of the indicia-defining pattern defined by said masking material.

7. The container of claims 2, 3, 4 or 6 wherein a primer layer operable to facilitate adhesion of said colorant is disposed between the transparent masking material and the colorant layer, the primer layer being disposed in an area at least coextensive with the area in which the colorant layer is disposed.

8. The container of claims 4 or 6 wherein the container is a flexible envelope.

9. The container of claims 4 or 6 wherein the container is a paper box.

10. An opaque flexible plastic envelope comprising:

(a) a body portion having a sealable surface and an integrated sealable closure flap, said closure flap having an exposed outer surface and a sealable inner surface;

(b) an aperture defined within an area of the closure flap registering with the sealable surface of the envelope upon closure of said flap;

(c) a translucent or transparent panel having an outer surface and an inner surface and possessing surface dimensions greater than those of said aperture such as to define a perimeter portion extending beyond the edges of the aperture, said panel overlaying said aperture and being affixed across at least a portion of its perimeter to the inner surface of the closure flap;

(d) a transparent masking material disposed (i) in an indicia-defining pattern (ii) on the inner surface of the translucent or transparent panel opposite the exposed outer surface of said closure flap and (iii) within an area registering with said aperture, said masking material possessing low adhesion properties to the material of said panel;

(e) a colorant layer disposed on the inner surface of said panel over the transparent masking material and extending beyond the indicia-defining pattern of the masking material;

(f) a primer layer operable to facilitate adhesion of said colorant to said panel disposed between said transparent masking material and said colorant layer in an area at least coextensive with the area in which said colorant layer is disposed; and

(g) a pressure sensitive adhesive disposed on said inner surface of the closure flap over and beyond the area in which said colorant layer and transparent masking material are disposed and operable upon closing said closure flap to seal the flap to a sealable surface of said envelope and upon unsealing of said flap to dislodge said colorant from said panel within the area of the indicia-defining pattern defined by said masking material for retention on said envelope sealable surface.

11. A seal comprising:

(a) a substrate having an outer surface and an inner surface;

(b) a transparent masking material disposed in an indicia-defining pattern on the inner surface of the substrate, said masking material possessing low adhesion properties to the material of said substrate;

(c) a colorant layer disposed on the inner surface of the substrate over the transparent masking material and extending beyond the indicia-defining pattern of the masking material; and

(d) an adhesive disposed over at least the area in which said colorant layer and transparent masking material are disposed.

12. The seal according to claim 11 wherein the seal is in the form of noncontinuous shapes. 5

13. The seal according to claim 11 further comprising a layer of release carrier web adjacent to the adhesive layer, the release carrier web comprising a material having a sufficiently low adhesion to the adhesive layer to enable the seal to be removed with substantially no disruption to the adhesive layer and the seal. 10

14. The seal according to claim 11 wherein the seal is in the form of a continuous strip. 15

15. The seal of claim 11 further comprising a barrier layer adjacent to the side of the adhesive layer opposite the colorant layer, and a strong adhesive layer adjacent to the side of the barrier layer opposite the adhesive layer, the barrier layer having greater adhesion to the strong adhesive layer than to the adhesive layer. 20

25

30

35

40

45

50

55

11

FIG-1




FIG-2




FIG-3




FIG-4




FIG-5




FIG-6




FIG-7




FIG-8




FIG-9




FIG-10




FIG-13




FIG-14




FIG-15




FIG-16




FIG-11




FIG-12




FIG-17




FIG-18




FIG-19





FIG-20





DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. Cl. 4)
A	GB-A-2 173 150 (DAIMATSU KAGAKU KOGYO) * Page 2, line 30 - page 3, line 38; page 6, line 52 - page 7, line 21; figures 1,2,10,11 * -----	1-4,6-7 ,10-11, 13-15	B 65 D 55/06 G 09 F 3/02 B 65 D 33/34 B 65 D 27/30
			TECHNICAL FIELDS SEARCHED (Int. Cl.4)
			B 65 D G 09 F
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 09-08-1989	Examiner BRIDAULT A.A.Y.
<div>CATEGORY OF CITED DOCUMENTS</div> <div><div>X: particularly relevant if taken alone Y: particularly relevant if combined with another document of the same category A: technological background O: non-written disclosure P: intermediate document</div><div>T: theory or principle underlying the invention E: earlier patent document, but published on, or after the filing date D: document cited in the application L: document cited for other reasons &: member of the same patent family, corresponding document</div></div>			